

Link do produktu: <https://www.sklep.caraudioteam.pl/audison-hv-venti-p-734.html>



Audison HV venti

Cena	35 829,00 zł
Dostępność	Na zamówienie
Producent	Audison

Opis produktu

Specyfikacja produktu:

- Power supply voltage: 11 ÷ 16 VDC
- Idling current when off: 0.006 mA
- Minimum idling current: Hi Curr. Hi Pow.
- Low BIAS 4.2A 5.6A
- High BIAS 6.5A 10.4A
- Consumption @ 13.8 VDC 90A(1Ω) 100A(2Ω)
- Distortion - THD (1kHz): <0.05%
- Distortion - IMD (IHF): <0.05%
- Bandwidth (-3 dB): 4Hz ÷ 75 kHz
- S/N Ratio (A weighed @1 V): 100 dB
- Damping factor (1kHz, 4 Ohms): 80
- Slew rate >20V/μs
- Input sensitivity (high): 0.25 ÷ 1.6 VRMS
- Input sensitivity (low): 1 ÷ 7 VRMS
- Input impedance: 22 kΩ
- Load impedance: Hi Curr. Hi Pow.
- Stereo 4 - 2 - 1Ω 4 - 2Ω
- Mono 4 - 2Ω 4Ω
- OUTPUT POWER (RMS) @13.8 VDC; THD 1%:
- Load (dual power) Hi Curr. Hi Pow.
- 2ch 4Ω 200W 400W
- 2ch 2Ω 400W 800W
- 2ch 1Ω 650W /
- Mono 4Ω 800W 1600W
- Mono 2Ω 1300W /
- Pre IN: L/R (ABS)
- Pre OUT (pre in bypass): L/R (ABS)
- Crossover frequencies High pass & Low pass stereo
- 45 - 55 - 65 - 80Hz, 12dB/oct.
- Lo-pass mono
- 45 - 55 - 65 - 80Hz, 24dB/oct.
- MAX SIZE (L x H x D): 510 x 85 x 280 mm
- WEIGHT: 15 Kg

