

Link do produktu: <https://www.sklep.caraudioteam.pl/audison-lrx-31k-p-739.html>



Audison LRx 3.1k

Cena **2 799,00 zł**

Dostępność **Dostępny**

Producent **Audison**

Opis produktu

Specyfikacja produktu:

- Power supply voltage: 11÷15 VDC
- Idling current: 2.6 A
- Idling current when off: 0.02 mA
- Consumption @ 14.4 VDC (Max Musical Power): 99 A
- Distorsion-THD(1kHz@4Ω)ACh: 0.08 %
- Distorsion-THD(100 Hz@4Ω)SubCh: 0.5 %
- Bandwidth (-3 dB) A Ch: 4 ÷ 62k Hz
- Bandwidth (-3 dB) Sub Ch: 7 ÷ 800 Hz
- S/NRatio(Aweighted@1V) A,Ch: 103 dB
- S/NRatio (A weighted@1V)SubCh: 87 dB
- Dampingfactor (1kHz@4Ω)ACh: 200
- Dampingfactor (100Hz@4Ω)SubCh: 110
- Input sensitivity: 0.3 ÷ 5 V
- Input impedance: 15k Ω
- Speaker-In sensitivity: 1.4 ÷ 24 V
- Speaker-In impedance: 5k Ω
- Load impedance MIN: 3 Ch x 2 Ω
- NOMINAL OUTPUT POWER (RMS) NP@12VDC;
- THD0.3%,1%A,SubCh: 140W x 2 + 625W x 1
- OUTPUT POWER (RMS) @ 14.4 VDC, THD 1%:
- • 3 Ch 170Wx2(4Ω)+750Wx1(4Ω)
- • 3 Ch 160Wx2(4Ω)+1150Wx1(2Ω)
- • 3 Ch 250Wx2(2Ω)+710Wx1(4Ω)
- • 3 Ch 250Wx2(2Ω)+1030Wx1(2Ω)
- In A Ch: Bypass / Hi-pass: 50 ÷ 150 Hz @ 12 dB/Oct.
- In Sub Ch: Bypass / Lo-pass: 50 ÷ 150 Hz @ 24 dB/Oct.
- Subsonic: OFF / 20 / 30 Hz @ 24 dB/Oct.
- BxLxH (mm/inches): 198 x 488 x 56 / 7"13/16x 19"1/4x 2"1/4
- Weight (kg/lb): 5,00 / 11.02

