

Link do produktu: <https://www.sklep.caraudioteam.pl/audison-lrx-31mt-p-740.html>



Audison LRx 3.1MT

Cena	3 099,00 zł
Dostępność	Dostępny
Producent	Audison

Opis produktu

Specyfikacja produktu:

- Power supply voltage: 11÷15 VDC
- Idling current: 2.2 A
- Idling current when off: 0.02 mA
- Consumption @ 14.4 VDC (Max Musical Power): 71.5 A
- Distorsion-THD(1kHz@4Ω)A,CentreCh: 0.03%
- Distorsion-THD(100Hz@4Ω)A,SubCh: 0.5 %
- Bandwidth (-3 dB) A, Centre Ch: 4 ÷ 58k Hz
- Bandwidth (-3 dB) Sub Ch: 4 ÷ 700 Hz
- S/NRatio(Aweighted@1V) A,CentreCh: 105 dB
- S/NRatio (A weighted@1V)SubCh: 85 dB
- Dampingfactor (1kHz@4Ω)A, CentreCh: 200
- Dampingfactor (100Hz@4Ω)SubCh: 90
- Input sensitivity: 0.3 ÷ 5 V
- Input impedance: 15k Ω
- Speaker-In sensitivity: 1.4 ÷ 24 V
- Speaker-In impedance: 5k Ω
- Load impedance MIN: 3Chx4Ω+1Chx2Ω
- NOMINAL OUTPUT POWER (RMS) NP@12VDC;
- THD0.3%,1%A, Centre,SubCh:95Wx 3+ 420W x 1
- OUTPUT POWER (RMS) @ 14.4 VDC, THD 1%:
- • 4 Ch 100 W x 3 (4Ω) + 460 W x 1 (4Ω)
- • 4 Ch 100 W x 3 (4Ω) + 800 W x 1 (2Ω)
- In A Ch: Bypass / Hi-pass: 30 Hz @12 dB/Oct.
- In Centre Ch: Bypass / Hi-pass: 30 Hz @12 dB/Oct.
- Subsonic: OFF / 20 / 30 Hz @24 dB/Oct.
- B x L x H (mm/inches): 198 x 488 x 56 / 7"13/16 x 19"1/4 x 2"1/4
- Weight (kg/lb): 5,00 / 10.02

