

Link do produktu: <https://www.sklep.caraudioteam.pl/jl-audio-10tw3-d4-10tw3-10tw3-4-10tw3-4ohm-p-3171.html>



JL AUDIO 10TW3-D4 10TW3 10TW3-4 10TW3-4ohm

Cena	2 499,00 zł
Dostępność	Na zamówienie
Czas wysyłki	5 dni
Producent	JL AUDIO

Opis produktu



[General Specifications](#)

Continuous Power Handling (RMS)	400 W
Recommended RMS Amplifier Power	200 - 400 W
Nominal Impedance (Znom)	Dual 4 Ω

[Physical Specifications](#)

Nominal Diameter	10 in / 250 mm
Overall Diameter (A)	A1: 11.2 in / 284 mm A2: 10.5 in / 267 mm
Mounting Hole Diameter (B)	9.625 in / 244 mm
Bolt Hole Circle (C)	10.5 in / 267 mm
Magnet Diameter (D)	5.1 in / 130 mm
Mounting Depth (E)	3.25 in / 83 mm
Driver Displacement	0.019 cu ft / 0.54 L
Net Weight	10.1 lb / 4.6 kg

Parameters

Free Air Resonance (Fs)	32.30 Hz
Electrical "Q" (Qes)	0.656
Mechanical "Q" (Qms)	11.35
Total Speaker "Q" (Qts)	0.62
Equivalent Compliance (Vas)	0.700 cu ft / 19.82 L
One-Way Linear Excursion (Xmax)*	0.6 in / 15.2 mm
Reference Efficiency (no)	0.2300%
Efficiency (1 W / 1 m)**	82.10 dB SPL
Effective Piston Area (Sd)	56.532 sq in / 0.0365 sq m
DC Resistance (Re)**	9.036 Ω