

Link do produktu: <https://www.sklep.caraudioteam.pl/jl-audio-10w6v3-d4-10w6v3-4-10w6v3-4ohm-p-3173.html>



JL AUDIO 10W6v3-D4 10W6v3-4 10W6v3 4ohm

Cena	4 499,00 zł
Dostępność	Na zamówienie
Czas wysyłki	5 dni
Producent	JL AUDIO

Opis produktu



Continuous Power Handling (RMS)
Recommended RMS Amplifier Power
Nominal Impedance (Znom)

600 W
200 - 600 W
Dual 4 Ω

[Physical Specifications](#)

Nominal Diameter	10.0 in / 250 mm
Overall Diameter (A)	10.5 in / 267 mm
Mounting Hole Diameter (B)	9.02 in / 229 mm
Bolt Hole Circle (C)	9.86 in / 250 mm
Magnet Diameter (D)	6.3 in / 160 mm
Required Pole Vent Clearance	0.50 in / 13 mm
Mounting Depth (E)	6.89 in / 175 mm
Driver Displacement	0.078 cu ft / 2.1 L
Net Weight	20 lb / 9.1 kg

Parameters

Free Air Resonance (Fs)	30.12 Hz
Electrical "Q" (Qes)	0.543
Mechanical "Q" (Qms)	9.228
Total Speaker "Q" (Qts)	0.513
Equivalent Compliance (Vas)	0.821 cu ft / 23.25 L
One-Way Linear Excursion (Xmax)*	0.75 in / 19 mm
Reference Efficiency (no)	0.1100%
Efficiency (1 W / 1 m)**	82.7 dB SPL
Effective Piston Area (Sd)	49.303 sq in / 0.0318 sq m
DC Resistance (Re)***	6.452 Ω