

Link do produktu: <https://www.sklep.caraudioteam.pl/jl-audio-12tw3-d4-12tw3-4-12tw3-4ohm-12tw3-4ohm-p-3172.html>



JL AUDIO 12TW3-D4 12TW3-4 12TW3 4ohm 12TW3-4ohm

Cena	2 699,00 zł
Dostępność	Na zamówienie
Czas wysyłki	5 dni
Producent	JL AUDIO

Opis produktu



[General Specifications](#)

Continuous Power Handling (RMS)	400 W
Recommended RMS Amplifier Power	200 - 400 W
Nominal Impedance (Znom)	Dual 4 Ω

[Physical Specifications](#)

Nominal Diameter	12 in / 300 mm
Overall Diameter (A)	A1: 13.2 in / 335 mm A2: 12.5 in / 318 mm
Mounting Hole Diameter (B)	11.625 in / 295 mm
Bolt Hole Circle (C)	12.5 in / 318 mm
Magnet Diameter (D)	6.125 in / 156 mm
Mounting Depth (E)	3.5 in / 89 mm
Driver Displacement	0.029 cu ft / 0.82 L
Net Weight	14.9 lb / 6.8 kg

Parameters

Free Air Resonance (Fs)	26.46 Hz
Electrical "Q" (Qes)	0.558
Mechanical "Q" (Qms)	10.766
Total Speaker "Q" (Qts)	0.531
Equivalent Compliance (Vas)	1.72 cu ft / 48.73 L
One-Way Linear Excursion (Xmax)*	0.6 in / 15.2 mm
Efficiency (1 W / 1 m)**	84.11 dB SPL
Effective Piston Area (Sd)	83.517 sq in / 0.0539 sq m
DC Resistance (Re)**	9.280 Ω