

Link do produktu: <https://www.sklep.caraudioteam.pl/jl-audio-12w6v3-d4-12w6v3-4-12w6v3-4ohm-p-3174.html>



JL AUDIO 12W6v3-D4 12W6v3-4 12W6v3 4ohm

Cena	4 999,00 zł
Dostępność	Na zamówienie
Czas wysyłki	5 dni
Producent	JL AUDIO

Opis produktu



General Specifications

Continuous Power Handling (RMS)	600 W
Recommended RMS Amplifier Power	200 - 600 W
Nominal Impedance (Znom)	Dual 4 Ω

Physical Specifications

Nominal Diameter	12.0 in / 300 mm
Overall Diameter (A)	12.5 in / 318 mm
Mounting Hole Diameter (B)	11.02 in / 280 mm
Bolt Hole Circle (C)	11.86 in / 301 mm
Magnet Diameter (D)	7.0 in / 178 mm
Required Pole Vent Clearance	0.50 in / 13 mm
Mounting Depth (E)	7.52 in / 191 mm
Driver Displacement	0.105 cu ft / 297 L
Net Weight	25.6 lb / 11.6 kg

Parameters

Free Air Resonance (Fs)	26.919 Hz
Electrical "Q" (Qes)	0.487
Mechanical "Q" (Qms)	9.365
Total Speaker "Q" (Qts)	0.463
Equivalent Compliance (Vas)	1.920 cu ft / 54.37 L
One-Way Linear Excursion (Xmax)*	0.75 in / 19 mm
Reference Efficiency (no)	0.1100%
Efficiency (1 W / 1 m)**	85.4 dB SPL
Effective Piston Area (Sd)	75.338 sq in / 0.0486 sq m
DC Resistance (Re)***	6.493 Ω