Dane aktualne na dzień: 29-03-2024 02:31

Link do produktu: https://www.sklep.caraudioteam.pl/jl-audio-3004v3-300-4v3-p-3207.html



JL AUDIO 300/4v3 300 4v3

Cena	**3 699,00 zł**
Dostępność	**Dostępny**
Producent	**JL AUDIO**

Opis produktu



Rated Continuous (RMS) Power @ 14.4 V

@ 4 Ω	75 W RMS x 4
@ 3 Ω	75 W RMS x 4
@ 2 Ω	75 W RMS x 4
@ 1.5 Ω	75 W RMS x 4
Bridged @ 8 Ω	150 W RMS x 2
Bridged @ 4 Ω	150 W RMS x 2

Rated Continuous (RMS) Power @ 12.5 V

@ 4 Ω	75 W RMS x 4
@ 3 Ω	75 W RMS x 4
@ 2 Ω	75 W RMS x 4
@ 1.5 Ω	75 W RMS x 4
Bridged @ 8 Ω	150 W RMS x 2
Bridged @ 4 Ω	150 W RMS x 2

General Specifications

Frequency Response	5 Hz - 30 kHz (+0, -1dB)
S/N Ratio, referred to highest rated power	>108.5 dB (A-weighted, 20 Hz - 20 kHz noise

	bandwidth)
S/N Ratio, referred to 1 W	>89.5 dB (A-weighted, 20 Hz - 20 kHz noise bandwidth)
Damping Factor @ 4 Ω	>300 / 50 Hz
THD+N @ Rated Power	<0.03% @ 4 Ω per Ch.
Input Voltage Range @ RCA Inputs	Switchable from 200 mV - 2 V RMS (Low) to 800 mV - 8 V RMS (High)
Min Copper Power / Ground Wire Gauge	4 AWG wire
Fuse Rating	40 A (AFS, AGU or MaxiFuse™)

Signal Processing

Filter Modes	Low-Pass or High-Pass
Filter Slope (dB/Octave)	12dB or 24 dB
Filter Frequency Range	50 Hz - 5 kHz
Detented, Calibrated Filter Freq. Potentiometers	Yes
Filter Defeatable?	Yes
Remote Level Control	No
Remote Level Modes	N/A
Channel Input Mode Switch	Yes (2/4 ch.)
Pass-Through Preamp Output Type	None
Source Channel Selection for PreOuts	N/A

Physical Specifications

Height (H)	2.36 in / 60 mm
Width (W)	13.40 in / 340 mm
Depth (D)	9.25 in / 235 mm