

Link do produktu: <https://www.sklep.caraudioteam.pl/jl-audio-slash-6001v3-600-1v3-6001v3-p-3206.html>



JL AUDIO SLASH 600/1v3 600 1v3 6001v3

Cena	3 999,00 zł
Dostępność	Dostępny
Producent	JL AUDIO

Opis produktu



[Rated Continuous \(RMS\) Power @ 14.4 V](#)

@ 4 Ω	600 W RMS x 1
@ 3 Ω	600 W RMS x 1
@ 2 Ω	600 W RMS x 1
@ 1.5 Ω	600 W RMS x 1

[Rated Continuous \(RMS\) Power @ 12.5 V](#)

@ 4 Ω	600 W RMS x 1
@ 3 Ω	600 W RMS x 1
@ 2 Ω	600 W RMS x 1
@ 1.5 Ω	600 W RMS x 1

[General Specifications](#)

Frequency Response	5 Hz - 250 Hz (+0, -1dB)
S/N Ratio, referred to highest rated power	>95 dB below rated power (A-weighted, 20 Hz - 20 kHz noise bandwidth)
S/N Ratio, referred to 1 W (Main Channels)	>68 dB (A-weighted, 20 Hz - 20 kHz noise bandwidth)

Damping Factor @ 4 Ω	>500 / 50 Hz
Damping Factor @ 2 Ω	>250 / 50 Hz
THD+N @ Rated Power (Main Channels)	<0.05% @ 4 Ω
Input Voltage Range @ RCA Inputs	Switchable from 200 mV - 2 V RMS (Low) to 800 mV - 8 V RMS (High)
Min Copper Power / Ground Wire Gauge	4 AWG wire
Fuse Rating	50 A (AFS, AGU or MaxiFuse™)

Signal Processing

Filter Modes	Low-Pass only
Filter Slope (dB/Octave)	12 dB or 24 dB
Filter Frequency Range	40-200 Hz
Detented, Calibrated Filter Freq. Potentiometer	Yes
Filter Defeatable?	Yes
Infrasonic Filter	Variable, Defeatable
Bass Boost EQ	Parametric
Output Polarity Switch	No
Remote Subwoofer Level Control	No
Remote Bass EQ Boost Control	Optional (RBC-1)
Pass-Through Preamp Output	Buffered, w/independent filter

Physical Specifications

Height (H)	2.36 in / 60 mm
Width (W)	13.40 in / 340 mm
Depth (D)	9.25 in / 235 mm