

Link do produktu: <https://www.sklep.caraudioteam.pl/rockford-fosgate-p1000x2-p-3720.html>



Rockford Fosgate P1000X2


Cena	3 300,00 zł
Dostępność	Na zamówienie
Producent	Rockford Fosgate

Opis produktu



CEA-2006 Compliant:	CEA-2006 Power Rating 300W x 2 @ 4Ω ≤1.0% THD+N
------------------------	--

Number of
Channels: 2



Rated Power (RMS Continuous Power):	300 Watts x 2 @ 4-Ohm 500 Watts x 2 @ 2-Ohm 1000 Watts x 1 @ 4-Ohm Bridged
---	--

Total Power (Sum of Rated Power):	1000 Watts RMS
---	----------------

Dynamic Power (PVC/PowerCube® Measurement):	401 Watts x 2 @ 4-Ohms 0° Res 656 Watts x 2 @ 2-Ohms 0° Res
---	--

Bridgeable:	Yes
--------------------	-----

Frequency Response:	20Hz to 20kHz +/- 1.0dB
----------------------------	----------------------------

Efficiency (average):	69% @ 4-Ohm 64% @ 2-Ohm
------------------------------	----------------------------

Total Harmonic Distortion (THD+Noise):	4-Ohm: <1.0% 2-Ohm: <1.0%
--	------------------------------

Crossover Controls:	High-Pass/Low-Pass (HP/LP): 50Hz-250Hz
----------------------------	---

12dB/octave
Butterworth

Tone Controls: Punch EQ2 Bass: 0dB to +18dB @ 45Hz and/or Punch EQ2 Treble: 0dB to +12dB @ 12.5kHz
Function depends upon LP/AP/HP switch position

Input Sensitivity: 150 mV - 12 V

Signal Input: *Hi/Low level:* 1 RCA pair

Signal Output: *Low level:* 1 RCA pair

Power Input Connector: Captive C-Clamp

Power Wire Gauge: 4 AWG

Speaker Captive C-Clamp

**Output
Connector:**

**Speaker Wire
Gauge:** 8 AWG to 18
AWG

**Heat Sink
Type:** Cast aluminum

Cooling: Convection

**Remote
Controls:** Optional Punch
Level Control
(PLC2) Ready

**Visual
Indicators:** Power/Protect/Th
ermal LED
Input Clip LED
Output Clip LED

**Circuit
Topology
Class:** Class-A/B

**Operating
Voltage:** 9 - 16 VDC

**Recommend
ed Fuse** 140 A
(not included)‡

Max. Current 140 A

Draw (13.8V

Sinewave):

Average 70 A

Current

Draw (13.8V

Music):

Suggested 100 A

Alternator:

Shipping 15 Lbs. (6.80 Kg.)

Weight:

Dimensions 2.38 x 7.76 x

(HxWxL): 15.03 (in)

6.05 x 19.71 x

38.18 (cm)

Dimensional

Diagram:

Clipping Calibrated Level Eliminates Audible Noise

Wzmacniacz deskartanowy z serii Punch. Możliwość modułowania. Zasewnoszone systemy ustawień. Wzmacniacz wyposażony jest w nowoczesny system C.L.E.A.R.

CLEAN to nowa zintegrowana technologia Rockforda sygnalizowana jest za pomocą diody i służy do ustawienia czułości wzmacniacza do sygnału wejściowego w celu zapobieżenia przed uszkodzeniem głośników. System wychwytuje przesterowania wejściowe i wyjściowe pozwalając na precyzyjne ustawienie czułości, co zapobiega uszkodzeniu głośników i daje czysty precyzyjny sygnał dźwiękowy.

W komplecie dołączona płyta do ustawienia CLEAN.

