

Link do produktu: <https://www.sklep.caraudioteam.pl/rockford-fosgate-p400x4-p-3739.html>



Rockford Fosgate P400X4

Cena	1 900,00 zł
Dostępność	Na zamówienie
Producent	Rockford Fosgate

Opis produktu



CEA-2006 Compliant:	CEA-2006 Power Rating 50W x 4 @ 4Ω ≤1.0% THD+N
------------------------	---

Number of
Channels: 4

Rated Power (RMS Continuous Power):	50 Watts x 4 @ 4-Ohm 100 Watts x 4 @ 2-Ohm 200 Watts x 2 @ 4-Ohm Bridged
---	---

Total Power (Sum of Rated Power):	400 Watts
---	-----------

Dynamic Power (PVC/PowerCube® Measurement):	82 Watts x 4 @ 4-Ohm 137 Watts x 4 @ 2-Ohm 266 Watts x 2 @ 4-Ohm Bridged
---	---

Bridgeable:	Yes
--------------------	-----

Frequency Response:	20Hz to 20kHz +/- 1.0dB
----------------------------	----------------------------

Efficiency (average):	67% @ 4-Ohm
------------------------------	-------------

Total Harmonic Distortion (THD+Noise):	4-Ohm: <1.0% 2-Ohm: <1.0%
--	------------------------------

Crossover Controls:	Front High-Pass/Low-Pass
----------------------------	--------------------------

(HP/LP):
50Hz-250Hz @
12dB/octave
Butterworth
*Rear High-
Pass/Low-Pass*
(HP/LP):
50Hz-250Hz @
12dB/octave
Butterworth
All-Pass: Yes

Tone Controls:	Front Punch EQ2 Bass: 0dB to +18dB @ 45Hz and/or Front Punch EQ2 Treble: 0dB to +12dB @ 12.5kHz Rear Punch EQ2 Bass: 0dB to +18dB @ 45Hz and/or Rear Punch EQ2 Treble: 0dB to +12dB @ 12.5kHz Function depends upon LP/AP/HP switch position
-----------------------	---

Input Sensitivity: 150 mV - 12 V

Signal Input: *Hi/Low level: 2*

RCA pair

**Signal
Output:** -

**Power Input
Connector:** Captive C-Clamp

**Power Wire
Gauge:** 8 AWG to 4 AWG

**Speaker
Output
Connector:** Captive C-Clamp

**Speaker Wire
Gauge:** 8 AWG to 18
AWG

**Heat Sink
Type:** Cast aluminum

Cooling: Convection

**Remote
Controls:** -

**Visual
Indicators:** Power/Protect/Thermal LED
Input Clip LED

Output Clip LED

Circuit Topology Class:	Class-A/B
--------------------------------	-----------

Operating Voltage:	9 - 16 VDC
---------------------------	------------

Recommended Fuse (not included):	60 A
--	------

Max. Current Draw (13.8v Sinewave):	60 A
--	------

Average Current Draw (13.8v Music):	30 A
--	------

Suggested Alternator:	75 A
------------------------------	------

Shipping Weight:	10.8 Lbs. (4.89 Kg.)
-------------------------	----------------------

Dimensions (HxWxL):	2.38 x 7.76 x 11.03 (in) 6.05 x 19.71 x 28.02 (cm)
----------------------------	---

Dimensional Diagram:

Clipping Calibrated Level Eliminates Audible Noise

Wzmacniacz czterokanałowy z serii Punch. Modułami możliwości. Zasilanie systemy ustawień. Wzmacniacz wyposażony jest w nowoczesny system C.L.E.A.N.

CLEAN to nowa zintegrowana technologia Rockforda sygnalizowana jest za pomocą diody i służy do ustawienia czułości wzmacniacza do sygnału wejściowego w celu zapobieżenia przed uszkodzeniem głośników. System wychwytuje przesterowania wejściowe i wyjściowe pozwalając na precyzyjne ustawienie czułości, co zapobiega uszkodzeniu głośników i daje czysty precyzyjny sygnał dźwiękowy.

W komplecie dołączona płyta do ustawienia CLEAN.