

Link do produktu: <https://www.sklep.caraudioteam.pl/rockford-fosgate-p600x4-p-3740.html>



Rockford Fosgate P600X4

Cena	2 600,00 zł
Dostępność	Na zamówienie
Producent	Rockford Fosgate

Opis produktu



CEA-2006 Compliant:	CEA-2006 Power Rating 75W x 4 @ 4Ω ≤1.0% THD+N
Number of Channels:	4
Rated Power (RMS Continuous Power):	75 Watts x 4 @ 4-Ohm 150 Watts x 4 @ 2-Ohm

300 Watts x 2 @
4-Ohm Bridged

Total Power 600 Watts
(Sum of Rated
Power):

Dynamic Power 129 Watts x 4 @
4-Ohms 0° Res
211 Watts x 4 @
(PVC/PowerCube®
Measurement): 2-Ohms 0° Res

Bridgeable: Yes

Frequency Response: 20Hz to 20kHz
+/- 1.0dB

Efficiency (average): 68% @ 4-Ohm

Total Harmonic Distortion 4-Ohm: <1.0%
2-Ohm: <1.0%
(THD+Noise):

Crossover Controls: Front/Rear High-Pass
(HP): 50Hz-250Hz
@ 12dB/octave
Butterworth
Front/Rear Low-Pass
(HP): 50Hz-250Hz
12dB/octave
Butterworth
All-Pass: Yes

Tone Controls:	Front Punch EQ2 Bass: 0dB to +18dB @ 45Hz and/or Front Punch EQ2 Treble: 0dB to +12.5dB @ 12kHz Rear Punch EQ2 Bass: 0dB to +18dB @ 45Hz and/or Rear Punch EQ2 Treble: 0dB to +12.5dB @ 12kHz Function depends upon LP/AP/HP switch position
-----------------------	---

Input Sensitivity: 150 mV - 12 V

Signal Input: *Hi/Low level:* 2 RCA pair

Signal Output: *Low level:* 1 RCA pair

Power Input Connector: Captive C-Clamp

Power Wire Gauge: 4 AWG

Speaker Captive C-Clamp

**Output
Connector:**

**Speaker Wire
Gauge:** 8 AWG to 18
AWG

**Heat Sink
Type:** Cast aluminum

Cooling: Convection

**Remote
Controls:** Optional Punch
Level Control
(PLC2) Ready

**Visual
Indicators:** Power/Protect/Thermal LED
Power/Protect/Thermal LED
Input Clip LED

**Circuit
Topology
Class:** Class-A/B

**Operating
Voltage:** 9 - 16 VDC

Recommended Fuse 100 A
(not included)‡

Max. Current 90 A
Draw (13.8V
Sinewave):

Average 45 A
Current
Draw (13.8V
Music):

Suggested 75 A
Alternator:

Shipping 12.8 Lbs. (5.80
Weight: Kg.)

Dimensions 2.38 x 7.76 x
(HxWxL): 13.28 (in)
6.05 x 19.71 x
33.73 (cm)

Dimensional
Diagram:

Wzmacniacz czterokanałowy z serii Punch. Możliwość monitorowania. Zasilane osiem systemów głośników. Wzmacniacz wyposażony jest w nowoczesny system C.L.E.A.N.

Clipping Calibrated Level Eliminates Audible Noise

CLEAN to nowa zintegrowana technologia Rockforda sygnalizowana jest za pomocą diody i służy do ustawienia czułości wzmacniacza do sygnału wejściowego w celu zapobieżenia przed uszkodzeniem głośników. System wychwytuje przesterowania wejściowe i wyjściowe pozwalając na precyzyjne ustawienie czułości, co zapobiega uszkodzeniu głośników i daje czysty precyzyjny sygnał dźwiękowy.

W komplecie dołączona płyta do ustawienia CLEAN.

